

VENTILATING FANS

AVION circulating fans ULTRA – the low-priced ventilation unit without the vibration.

ULTRA fans are made of heat-resistant alloy RA 330. ULTRA ventilating fans are always heat treated, x-rayed and examined for smooth operation prior to delivery.

The life of the fans of 520 mm and 610 mm may be considerably increased by reduction of the motor revolutions to 750 rpm.

EXTENT OF SUPPLY / DIAMETER:

18 1/2 "	470 mm
20 1/2"	520 mm
24"	610 mm

MATERIAL:

Heat-resistant stainless steel, US standard RA 330 (1.4864)



AVION ventilating fan ULTRA

All circulating fans are always available ex stock.

COMPANY PROFILE

GRAFBOARD®

BIIDNED CYCTEMS

SI/SIC RADIANT TURES

FINNED RADIANT TUBES

MUFFLES

FURNACE CHAINS

VENTILATING FANS

STOP-OFF COATINGS
BURNER TIPS
SPYROCOR™

MOTOR WITH COOLING FLANGE 2 speed settings



5 kW	1430 rpm	10,9 A
1,7 kW	960 rpm	4,7 A

suitable for fan diameters

Ø 480 mm	Ø 530 mm	Ø 610 mm

the wird af charge

AVION Manufacturing Company

879 S. Progress Drive, Unit D Medina, Ohio 44256

phone (330) 220-2779 fax (330) 220-3709 web www.avionmfg.com e-mail info@avionmfg.com